


REFRIGERATORS - FEATURES & SPECIFICATIONS				
	1896 Bottom Mount	1898 French Door Full Depth	1899 French Door Counter Depth	
CAPACITY				
Total Fridge & Freezer (cu. ft.)	18.5	25.0	20.0	
Total Freezer (cu. ft.)	5.73	7.44	5.62	
Total Fridge (cu. ft.)	12.94	17.75	14.38	
REFRIGERATORS / FREEZER FEATURES				
Fully adjustable shelving	•	•	•	
Gallon size adjustable door storage	•	•	•	
Sealed vegetable crisper with adjustable humidity control	•	•	•	
Deli bin		•	•	
Crispers and bins made of clear durable Lexan™				
Beverage rack	•		•	
Slide out upper freezer basket				
	•		•	
Separate fridge / freezer controls	•			
Internal filtered water dispenser	N/A	•	•	
Factory installed ice maker	Optional	Standard	Standard	
EnergyStar	•	•	•	
Energy Guide (US) / EnerGuide (CDN) Rating (KwH/yr.)	521 / 441	615 / 449	563 / 405	
Shipping weight (lb.)	370	460	400	
CABINET FEATURES				
Injection molded fiberglass doors with enamel coating	•	•	•	
Adjustable rollers provide easy movement for cleaning	•	•	•	
Sculptured door handles	•	•	•	
Coil free back, clean-free condenser	•	•	•	
Left hand hinge	Optional	N/A	N/A	
COLORS				
Standard - Black, White, Bisque, Cayenne Pepper Red, Liberty Blue	•	•	•	
Premium - Black/White combination, Black/Bisque combination	•	•	•	
Standard Door Handles	Nickel	Nickel	Nickel	
Antique Copper door handles	Optional	Optional	Optional	
Nickel or Antique Copper door frames	Optional	Optional	Optional	
DIMENSIONS - See diagram on facing page				
A Height to top of door	67 1/4"	69 %"	69 1/8"	
Height to top of hinge	66 ½"	69 %"	69 1/8"	
B Height to top of case	65 3/4"	68 5/8"	68 5/8"	
C Depth not including door	28 1/4"	29"	24"	
D Depth including door	33 3/4"	34"	29"	
E Depth including door and handles	33 3/4"	35 3/8"	30 3/8"	
F Depth with door(s) open 90 degrees	59 1/2"	48 1/4"	43 1/4"	
G Depth with freezer drawer open	52 ½"	54 ³ / ₄ "	46"	
H Width of case	29 1/4"	35 5/8"	35 5%"	
	30"	36"	36"	
Width with door(s) Width with door(s) appn 90 dogrees (not incl. handle)				
Width with door(s) open 90 degrees (not incl. handle)	32 1/4"	42 7/8"	42 7/8"	
Side clearance from wall for doors to open 90 degrees	2 1/2"	4"	4"	
Cutout dimensions:				
Width	30"	36"	36"	
Height	67"	70"	70"	
Minimum depth	24"	24"	24"	
Ideal depth	28"	28"	24"	

REFRIGERATOR DIMENSIONS







MICROWAVES & WALL OVENS - FEATURES & SPECIFICATIONS				
	1895 Microwave	1880 Wall Oven		
APACITY				
	2.2 cu. ft.	5.0 cu. ft.		
VERALL DIMENSIONS:				
Height	14"	30 1/4"		
Width	24"	30"		
Depth	20"	24"		
Depth with Doors, Ash Catch		30"		
ABINET CUT-OUT DIMENSIONS (Minimum)*				
Height	14-1/4"	28"		
Width	24-1/4"	28-1/2"		
Cabinet Width		30"		
Depth	24"	24"		
Rear Stop Depth	15-1⁄2"	N/A		
OWER SOURCE				
	120V, 15A	220V, 30A		
HIPPING WEIGHT				
	65 lb.	150 lb.		
MICROWAVE OVEN NOTES:				

Model 1895 is designed as a countertop unit. If built into cabinets, allow a minimum total of 30 square inches of ventilation space around the face of the unit – top, sides and bottom. This can be accomplished with open space, louvers, slots, etc.

*WALL OVEN NOTES:

Allow 5 ¼" minimum from bottom of cutout to floor. Allow 1½" minimum from top of cutout to underside of counter-top. Wall ovens can be installed two high.